



(19)

(11) Publication number: **6.**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **62130765**(51) Intl. Cl.: **H01P 5/22**(22) Application date: **27.05.87**

(30) Priority: (43) Date of application publication: <b>30.11.88</b> (84) Designated contracting states:	(71) Applicant: <b>FUJITSU LTD</b> (72) Inventor: <b>NAKATANI TETSUJI</b> (74) Representative:
--	--

**(54) THREE-BRANCH LINE  
3DB HYBRID CIRCUIT**

(57) Abstract:

**PURPOSE:** To improve the isolation characteristic of a three-branch line 3dB hybrid circuit, by adding capacities to the branched sections of lines and making the center frequency for degree of coupling coincident with the center frequency for isolation.

**CONSTITUTION:** This three-branch line 3dB hybrid circuit is composed of 1st lines 5 and 8 and 2nd lines 6 and 7 which are connected in series with input-and output-side lines 1 ~ 4 and lines 9 ~ 11 which are connected in parallel with the lines 5 ~ 8. By making the impedance of the 1st and 2nd lines 5 and 8 and 6 and 7 equal to the impedance of the input-and output-side lines 1 ~ 4 and adding projecting patterns 12 ~ 15 to the 1st and 2nd lines 5 and 8, and 6 and 7, in the vicinity of the branched sections of the lines 9 and 11 on the input and

output sides of the parallel three lines 9~11, the frequency for degree of coupling is made coincident with the frequency for isolation. Therefore, the isolation characteristic can be improved.

COPYRIGHT: (C)1988,JPO&Japio

